




# FP1 MOC



## Tipi di cucitura Sewing types




 Macchina piana a due aghi, trasporto a griffa saltellante, piedino a rotella per filati pesanti e cuciture ornamentali.

### CAMPO D'IMPIEGO

Macchina piana a due aghi per filati pesanti, realizzata per la cucitura del finto mocassino o per cuciture ornamentali su pelli integrali e crosta medio-pesante o pesante come valigie, borse porta attrezzi, borse da viaggio o tessuti pesanti come jeans, tendoni parasole e salotti.

### CARATTERISTICHE TECNICHE

- Velocità max cucitura ..... 800/900 r.p.m.
- Max lunghezza punto ..... 8,0 mm
- Distanza aghi ..... 3,0 - 7,0 mm
- Tipo ago ..... 328
- Finezza ago ..... 140/220
- Diametro filato (min-max) ..... 0,6 - 1,2 mm
- Voltaggio ..... 220 V - 50/60 Hz
- Dimensioni ..... 105x55x115
- Peso ..... ~ 110kg

 Flat-bed sewing machine, double needle with drop feed, roller presser for thick threads and ornamental stitchings.

### AREA OF APPLICATION

Flat-bed sewing machine, double needle with drop feed and roller presser for thick threads, projected to sew mock moccasin or for ornamental stitchings on integral leathers and thick leather for cases, tool bags, suitcases or thick materials like jeans, awnings and sofas.

### TECHNICAL FEATURES

- Max sewing speed ..... 800/900 r.p.m.
- Max stitch length ..... 8,0 mm
- Needles gauge (min-max) ..... 3,0 - 7,0 mm
- Needle type ..... 328
- Needle thickness ..... 140/220
- Thread diameter (min-max) ..... 0,6 - 1,2 mm
- Voltage ..... 220 V - 50/60 Hz
- Sizes ..... 105x55x115
- Weight ..... ~ 110kg